

MAG

HOT FOIL MARKING TAPE



We are an ISO 9001:2015 certified manufacturer and exporter of **HOT FOIL MARKING TAPES** in India. These tapes are used in **Wire & Cable Industries** and **Plastic Pipe Manufacturing Industries** to emboss & print company name, logo, product specifications, data and meter length. We are also manufacturing **Tamper Evident Tape** and **Marking Tape for Tyre Industries**.

www.magplastics.com

TECHNICAL SPECIFICATIONS

BASE SUBSTRATE	12 micron Polyester Film
TENSILE STRENGTH	More than 11 Kg. / mm ²
ELONGATION	More than 60%
RESISTANCE PROPERTY OF EMBOSSED PRINT	Embossed print is resistant to water, Scrubbing and Erosion in extreme Weather conditions. (-40°C to +55°C)
SHELF LIFE	2 Years
TEMP. REQUIRED FOR EMBOSSING	55°C to 90°C at metal block (Best results can be achieved by adjusting Temperature and pressure)

FEATURES:

- Bright and sharp emboss printing.
- Requires low temperature for printing.
- Suitable for high speed lines.
- Print is durable, resistant to water and scrubbing.
- No dust formation on substrate or on machine.
- Suitable in all weather conditions.

COLORS AVAILABLE

- White, Yellow, Orange, Red, Green, Blue, Black and Metallic Gold & Silver.

WIDTH / SIZE AVAILABLE:

- 6mm, 7mm, 8mm, 9mm, 10mm, 12mm, 15mm
- Any other size of customer choice upto 650mm.

LENGTH IN ROLL:

Pan Cake

- 610 meters, 900 meters, 1000 meters, 1200 meters, 1500 meters, 2000 meters, 2500 meters and 3000 meters.

Traverse Wound Spool

- 15000 meters (15 Kms.), 17000 meters (17 Kms.), 20000 meters (20 Kms.)

CORE ID :

Pan Cake

- 26 mm, 38 mm and 76 mm.

Traverse Wound Spool

- 20.5 mm
- 9 mm

MAG Plastics

Works : K-451 & 480, DSIIIC Bhorgarh Industrial Area
Bawana Phase-II, New Delhi-110040 INDIA

Correspondence Address : Ground Floor, Village Bhorgarh
Main Alipur-Narela Road, Opp. Govt. School
Near Main Bhorgarh Bus Stand, New Delhi-110040

magplastics@gmail.com, magplastics@rediffmail.com

www.magplastics.com, www.magplastics.co.in



Tyre Run Out Marking Tape



Tamper Evident Tape